

# BAKO VISION

## BR Series

Round Shape LED Sign,  
Digital Round Logo Sign

Outdoor Rated  
High Bright and IP 65  
Front Access, Double Sided  
Plug & Play Solution




### Outdoor Rated

- › Water proof and high bright
- › For all weather conditions




### Round & Oval Options

- › Round and Oval shape options
- › Both double sided



### Easy to Install & Maintain

- › Smart bracket design
- › Front access
- › Less than 20 kg



### Plug & Play Solution

- › WIFI, USB, Cloud platform
- › Plug & Play solution



## Round Shape / Specifications

	BR(Round)-4.68	BR(Oval)-8
Physical Pitch	4.68 mm	8 mm
Pixel Configuration	SMD 3-in-1	SMD 3-in-1
Pixel Density	45511 pixel/m <sup>2</sup>	15625 pixel/m <sup>2</sup>
Module Dimensions (W × H) (mm)	300 × 300	320 × 320
Inner-Diameter (mm)	600	960 × 640
NO.of Modules Per Panel (W × H)	2 × 2	2 × 2
Physical Resolution of Module (W × H)	64 × 64	40 × 40
Screen Resolution (W × H)	128 × 128	120 × 80
Panel Material	Steel	Steel
Single Cabinet Weight	16 kg / unit	19 kg / unit
Colours	281 trillion	281 trillion
Contrast Ratio	2000:1	2000:1
Power Consumption	around 400 W / unit	around 400 W / unit
Driving Method	1/8 Dynamic Scan	1/8 Dynamic Scan
Operating Temp/Humidity	-20° - 60°C / 10% - 95%	-20° - 60°C / 10% - 95%
Brightness	>4,500 nits	>4,500 nits
Brightness Adjustment	Manual Adjustment	Manual Adjustment
Control Method	WIFI / USB/ Cloud Platform	WIFI / USB/ Cloud Platform
Refresh Rate	≥1,920 Hz	≥1,920 Hz
Working Voltage	Ac 240/100 ± 10%, 50 Hz/60 Hz	Ac 240/100 ± 10%, 50 Hz/60 Hz
Vertical Viewing Angle	120°	120°
Horizontal Viewing Angle	120°	120°
IP Rating (Front/Rear)	IP65	IP65
Expected Lifetime	100,000 Hrs	100,000 Hrs
Servicing	Front	Front

## Typical Applications:

- Club
- Car Show
- Bar
- Shopping Mall
- Fashion Store
- Opera House
- DJ Touring
- House of Worship
- Wedding Hall
- Theme Resort
- Night Club
- Dancing Hall